

TECHNICAL SPECIFICATIONS

Stereo Specifications

General	Physical dimensions	Stereo dimensions (HxWxD): 5.1" x 5.1" x 2.2" (130 x 130 x 56 mm)
	Weight	16.75 oz (475 g)
	Power input	10.8–16 VDC
	Operating temperature range	32-122 degrees F (0-50 degrees C)
	Current (max)	15 A
	NMEA 2000® network LEN	1 (50 mA)
	BLUETOOTH [®] technology wireless range	Up to 30' (10 meters)
	ANT® connectivity wireless range	Up to 10' (3 meters)
	Wireless frequencies/protocols	BLUETOOTH 2.4 GHz @+12 dBm nominal ANT 2.4 GHz @+7 dBm nominal
	Compass-safe distance	5.9" (150 mm)
Stereo Features	Built-in amplifier	Class-D (2 ohm stereo-stable)
	Peak power	280 watts
	Rated power output (2 ohm)	43 watts RMS x 4 @14.4 V input < 10% THD
	Rated power output (4 ohm)	26 watts RMS x 4 @14.4 V input < 10% THD
	Built-in Digital Signal Processing	Yes (with preconfigured DSP profiles)
	PartyBus™-Network capabilities	Yes (wired)
	Fusion-Link™ control	Yes (with MFD, smartphone and Garmin® watch)
	Multi-Zone™ technology	4 zones
	Built-in Wi-Fi® technology	No
	BLUETOOTH wireless technology	Yes
	ANT wireless technology	Yes
	SiriusXM⊚ ready	Yes (requires SiriusXM Connect vehicle tuner)
	DAB+ radio ready	Yes (requires DAB100A antenna module)
	Optical audio input	Yes
	NRX remote compatibility	Yes
	Software updates	Over-the-air software updates via the Fusion-Link app¹ USB
	Warranty	3 years
Sources	Sources	AM/FM/BLUETOOTH/AirPlay® 2 from Apple®1/digital optical input/USB audio/ iPhone®/iPod®/AUX x1/universal plug-and-play¹/MTP/SiriusXM ready (U.S. only; requires optional SiriusXM Connect vehicle tuner)/DAB+ ready (available in Europe and Australia only)
Connectivity	Auxiliary input	One RCA input (AUX)
	Optical audio input	One digital optical input (SPDIF) port
	Ethernet	One Ethernet port
	NMEA 2000	One NMEA 2000 port
	USB 2.0	One USB 2.0 port
	SiriusXM satellite radio	One SiriusXM port (requires SiriusXM Connect vehicle tuner; does not support traffic and weather)
	AM/FM radio	One Motorola antenna connector port
	Speaker	4 x speaker connections (2 zone amplified)
	RCA pre-out (left, right and subwoofer)	4 zones (requires external amplification)
	Line out	4 (1 x L + R per zone; requires external amplification)
	Subwoofer out	1 x mono output (requires external amplification)